




## HydroMassage Home Installation Requirements – 60Hz, USA


### Technical Specifications

MODEL	IMAGE	SPECS	WEIGHT	WATER	VOLTAGE	PHASE	Amps
HM200 Lounge		91" L x 32" W x 46" H	285 lbs empty. 385 lbs with water	12 gallons distilled water	208-240 Volts	Single	30 Amp


**Water Requirements:** 12 gallons of distilled water is required. Distilled water is available at major supermarkets or directly from a water delivery service.

**Electrical Requirements** \*Contact a licensed electrician to install the electrical outlet

- 220V Electrical: 208-240 Volt, single-phase, dedicated line with a 30 Amp dedicated breaker and 10-gauge wire (two hot legs and a ground). Install 6" above the floor. Locking Receptacle: 30 Amp, 250 Volt NEMA L6-30R Locking Receptacle (three prong plug).
- Internet connection. A strong Wi-Fi or wired internet connection is required for software updates and remote technical support



**NEMA L6-30R  
Locking  
Receptacle**



**When Possible, the  
Electrical Outlet  
Should be Installed  
Behind Unit on Wall**

### Installation and Care FAQs

How do I get the required 220V electrical outlet installed? Any licensed electrician in your area should be able to provide a quote to install the 220V electrical outlet for HydroMassage.

How much can I use HydroMassage at home? The HydroMassage HM200 was designed to be used on a limited basis at home. After 30-minutes of use per hour, a 30-minute cooldown is required.

Can I use this in a commercial business? No, the HM200 is not designed to withstand commercial use, and any usage outside of a residential setting will void the warranty.

Do I need a plumbing source for HydroMassage? HydroMassage operates with 12 gallons of distilled water, and no plumbing hook-up is required.

Will HydroMassage heat up the room? Yes, HydroMassage units produce up to 5,000 BTU of heat while in use. Additional cool airflow into the room is helpful to maintain a comfortable temperature.

Is any maintenance required? We recommend draining and cleaning the HydroMassage unit 1X per year. Depending on usage, the rubber membrane should be replaced every 2 years (\$248).

Are service techs available for the annual cleanings? Yes, we have a network of independent techs around the country that may be hired to complete the recommend annual service for you if desired.

What happens if HydroMassage leaks? The tank has a holding reservoir under the unit which would hold all 12 gallons of water in the event of a leak.